



EXCELLO BOILER COMPOUND

FOR TREATMENT OF WATER IN HEATING PLANTS

DEFIANCE EXCELLO BOILER COMPOUND is designed for use as an internal treatment for the prevention of scale and corrosion in steam boilers.

FEATURES

- ◆ 100% Soluble in Water
- ◆ Helps prevent foaming, priming and carryover
- ◆ Peptizing action aids in preventing sludge problems
- ◆ Helps prevent caustic embrittlement by controlling boiler water alkalinities
- ◆ Causes precipitate to form for easy clean-up

Directions For Use:

1. Flush boiler thoroughly to remove loose scale and sludge.
2. Fill boiler with fresh water to operating level. Add enough Excello Boiler Compound to reach a ph of 11 or above.
3. Operate boiler. Check ph of Boiler– blow down water once a day. Add enough Excello Boiler Compound to maintain boiler water at a ph of 11 or add 1/2 gallon of Excello Boiler Compound to each 200 gallons of water.
4. Blow down boiler once each day for one minute to maintain boiler water solids at proper concentration.

Packaged in 55 and 30 gal. drums 5 gal. pails and 6x1 gallon cases

Since 1924

Omaha Compound Company

2001 Nicholas Street ♦ Omaha, Nebraska 68102

Tel: 402-346-7117 ♦ Fax: 402-346-2040
